





Fatigue-Step Floor Tiles


Anti-Slip floor tiles for wet and oily areas





- Interlocking open-holed floor tiles for general industrial use.
- Soft, yet resilient rubber floor tiles.
- Offers effective Anti-Fatigue properties for prolonged standing.
- Fatigue-Step conforms to Slip Resistance Test EN 13552 Category R10.
- Samples are available on request for pre-qualified leads and resellers only.



Edging comes in both Male and Female versions. Both versions have an attached corner piece that can be trimmed to allow for continuous edging.



Example:
 2 x 750 (L) x Cut; 3 x Female Edge; 3 x Male Edge.
 Area covered = 1.09m²



Parts

Part Number

Size

Colour

Weight (kg)

Part Number	Size	Colour	Weight (kg)
SS010001	900mm x 900mm x 19mm	Black	11.5kg
SS010006	900mm x 900mm x 14mm	Black	9kg
SS010002F8 (Female Corner Edge)		Black	1kg
SS070002F (Female Corner Edge)		Yellow	1kg
SS010002M (Male Corner Edge)		Black	1.3kg
SS070002M (Male Corner Edge)		Yellow	1.3kg

☎ 016 976 7001

✉ sales@tharochem.co.za

🌐 www.tharochem.co.za

📍 14 William Stow St, Sasolburg

